
MHS Heavy-Duty Secondary Belt Cleaner

Superior Cleaning on the Toughest Belts

The MHS Heavy-Duty Secondary Belt Cleaner was designed to deliver and maintain superior cleaning efficiency, even on the most demanding, abusive beltlines. The MHS is the new answer to tough belt cleaning problems. It delivers high-efficiency cleaning, long-lasting performance—and with low maintenance.



Features and Benefits

- Cleaning efficiency of metal blades. The thin, hard edges of the metal blades deliver high cleaning efficiency and long wear life.
- Works with Flexco mechanical splices. The C-Tip tungsten carbide blades are impact-resistant, and the spring cushion allows them to move away from a passing splice without damage and with minimal cleaning disruption. V-Tips can be used only on vulcanized belts.
- A complete cleaning system. When the MHS is teamed with the MMP precleaner the system provides maximum cleaning power for tough applications.
- Made for mining conveyors. Made from heavy-duty, corrosion-resistant steel, the MHS is available in sizes for belt widths from 24" to 84" (600 to 2100 mm). Additional sizes are available upon request.
- Safe to service. All service can be performed from a safe position at the side of the conveyor.



MHS Heavy-Duty Secondary Belt Cleaner

Specifications and Guidelines

Maximum Belt Speed

1200 FPM (6 M/sec)

Temperature Rating

-30° F to 180° F (-35° C to 82° C)

Usable Blade Wear Length


3/8" (9 mm)

Blade Material

Impact resistant, long-lasting tungsten carbide (C-Tip for mechanical fasteners, V-Tips for vulcanized belts)


Available for Belt Widths

18" to 84" (450 to 2100 mm)



Pole Length Cleaner size + 54" (1350 mm)

Maximum Conveyor Span Cleaner size + 44" (1100 mm)



Horizontal Clearance Required 4" (100 mm) Vertical Clearance Required

9-1/2" (238 mm)

Ordering Information

MHS HD Secondary with C-Tips					
Belt Width		Ordering	Item		
in.	mm	Number	Code		
24	600	MHS-24	75910		
30	750	MHS-30	75911		
36	900	MHS-36	75912		
42	1050	MHS-42	75913		
48	1200	MHS-48	75914		
54	1350	MHS-54	75915		
60	1500	MHS-60	75916		
72	1800	MHS-72	75917		
84	2100	MHS-84	76803		

MHS HD Secondary with V-Tips*							
Belt Width		Ordering	Item				
in.	mm	Number	Code				
18	450	MHS-18V	76169				
24	600	MHS-24V	76170				
30	750	MHS-30V	76171				
36	900	MHS-36V	76172				
42	1050	MHS-42V	76173				
48	1200	MHS-48V	76174				
54	1350	MHS-54V	76175				
60	1500	MHS-60V	76176				
72	1800	MHS-72V	76177				
84	2100	MHS-84V	76804				

^{*}V-Tips can be used ONLY on vulcanized belts

MHS with Air/Water Tensioner*							
Belt Width		Ordering	Item				
in.	mm	Number	Code				
24	600	MHS-24A	76604				
30	750	MHS-30A	76605				
36	900	MHS-36A	76606				
42	1050	MHS-42A	76607				
48	1200	MHS-48A	76608				
54	1350	MHS-54A	76609				
60	1500	MHS-60A**	76610				
72	1800	MHS-72A**	76611				
84	2100	MHS-84A**	76612				
Includes Central Pov							

^{*}Includes Control Box

MHS Reversing with C-Tips						
Belt Width		Ordering	Item			
in.	mm	Number	Code			
24	600	MHS-24R	76613			
30	750	MHS-30R	76614			
36	900	MHS-36R	76615			
42	1050	MHS-42R	76616			
48	1200	MHS-48R	76617			
54	1350	MHS-54R	76618			
60	1500	MHS-60R	76619			
72	1800	MHS-72R	76620			
84	2100	MHS-84R	76621			

MHS Reversing with V-Tips*							
Belt \	Vidth	Ordering	Item				
in.	mm	Number	Code				
18	450	MHS-18RV	76646				
24	600	MHS-24RV	76647				
30	750	MHS-30RV	76648				
36	900	MHS-36RV	76649				
42	1050	MHS-42RV	76650				
48	1200	MHS-48RV	76651				
54	1350	MHS-54RV	76652				
60	1500	MHS-60RV	76653				
72	1800	MHS-72RV	76654				
84	2100	MHS-84RV	76805				

^{*}V-Tips can be used ONLY on vulcanized belts

Replacement Tips					
Ordering Number	Item Code				
ICT6	74535				
RSA150	73628				

Tips Required Per Cleaner Size										
in.	18	24	30	36	42	48	54	60	72	84
mm	450	600	750	900	1050	1200	1350	1500	1800	2100
C-Tips or V-Tips Required	3	4	5	6	7	8	9	10	12	14

Authorized Distributor:



2525 Wisconsin Avenue • Downers Grove, IL 60515-4200 U.S.A.
Tel: (630) 971-0150 • Fax: (630) 971-1180 • E-mail: info@flexco.com • Web: www.flexco.com

Australia: 61-2-9680-3322 • China: 86-21-33528388 • England: 44-1274-600-942 • Germany: 49-7428-9406-0 India: 91-44-4354-2091 • Mexico: 52-55-5674-5326 • Singapore: 65-6281-7278 • South Africa: 27-11-608-4180

FLEXCO

^{**60&}quot;, 72" and 84" models have a 3-piece pole.